

# Cut / Needle Resistant Gloves



Level 9 Cut Protection / Needle Resistant

Part# KE-GL60-S  
Part# KE-GL60-M  
Part# KE-GL60-L  
Part# KE-GL60-XL  
Part# KE-GL60-2XL

Highly durable synthetic leather palm. 10 times more durable than normal synthetic leather

Needle resistant material in the palm



Protection zones (Palm side only)

Color coded cuff for easy identification

## Applications:

- ▶ Metal sorting
- ▶ Recycling
- ▶ Glass handling
- ▶ Wood processing
- ▶ Anywhere that serious hand protection is needed

## Features:

- ▶ High comfort and dexterity factor
- ▶ Tested in accordance with ASTM F2878-10 and ISO 13997
- ▶ Provides industry leading needle resistance

## Needle Resistance:

- ▶ Palm: 12.8 Newtons (needle bent)
- ▶ Fingers: 8.7 Newtons
- ▶ Classification Level (#): A9
- ▶ ISO13997: LEVEL F
- ▶ EN388-2016 Puncture resistant: Performance 151-198 N. Level 4
- ▶ Hypodermic Needle Puncture Resistance (ANSI/ISEA 105-2016, 5.1.3 & ASTM F2878-10) - Needle Size: 25 Gauge (0.5 mm)
- ▶ Level 9



Railhead Corp.  
224 Shore Court, Burr Ridge, IL 60527  
800-235-1782 708-844-5500  
[www.railheadcorp.com](http://www.railheadcorp.com)