Also used as an emergency lighting replacement. Meets requirements of 49 CFR 238.115 and APTA SS-E- 013-99 Rev 1

3.2 Watt Emergency LED Lamp

Description:

Extremely rugged internal construction built to conform to AAR LED LAMP SPEC requirements: The lamp shall operate under vibration of 2.5G at 2 to 44 hertz (in any direction) and shock of 3G for 0.015 seconds (in any direction).

Solid-state lighting is now available to replace the 30 Watt bayonet base bulb. Incorporated heat sink maximizes LED life.

Features:

- EMI quiet / does not cause radio interference
- Eliminates cut and burn injuries
- Anti-theft DC circuit (will not work on household power)
- Warranty: 3 years

Specifications:

Operating Voltage	75VDC (or custom)
Rated Life	50,000 hours
Color Temperature	6000K
Brightness	300 lumens
Power Consumption	3.2W
Base Material	Aluminum Alloy, PVC Cover
Operating Temp	-40°F to +90°F
Base	BA15D
Size	1" x 1" or 1" x 2.5" available
Case Quantity	100

KE-MCC









Light Quality Comparison





Incandescent

KE-MCC

Railhead Corp. 224 Shore Court, Burr Ridge, IL 60527 800-235-1782 708-844-5500 www.railheadcorp.com

