

RAILHEAD CORPORATION

LED Explosion Proof Work Light

RH-EXRWL

Ex

LED

IP
66



Lifter

Flood-60°

EXPLOSION RATING: Ex de IIc T6Gb

- Class: 1+2, DIV. 1+2
- Gas zones: 0, 1, 2
- Dust zones: 20, 21, 22

CHARACTERISTICS

- Flood light pattern.
- Safe and reliable: flame proof protection. Suitable to be used in various flammable and explosive environments.
- Efficient & Energy-saving: CREE LED light source, with 100,000 hours service life. It has battery level indicator.
- IP66 rating makes this suitable to be used in all kinds of harsh environments.
- Flexible & Convenient: The lamp head has 360° rotation and 135° tilt.
- Extendable pole 3.11 to 5.5 ft.
- Wheels on the bottom make the transportation easy.
- Intelligent charging: The charger is protected against, over-charging, over discharge and short circuit. When battery is fully charged, it will switch to trickle charging automatically when battery is fully charged.

MAIN SPECIFICATION

| Specification | | | |
|---------------------------------|----------|-------------|-----------|
| Rated voltage | V | 24 | |
| Rated capacity | Ah | 15 | |
| Rated power | W | 30 | |
| Light output (high/low) | lm | 2300 / 1600 | |
| Average service life | h | 100,000 | |
| Continuous runtime (high / low) | h | 16 / 36 | |
| Recharge time | h | 12 | |
| Effective beam distance | ft | | 492 |
| Service life of battery | Recycled | ≈ 1000 | |
| Dimension | L×W×H | ft | 1 × 1 × 2 |
| Net weight | lbs | 31 | |



Railhead
GEAR

Railhead Corp.
224 Shore Court, Burr Ridge, IL 60527
800-235-1782 708-844-5500
www.railheadcorp.com